

Pedestal C I

incl. Dolly DV 75, pump



C I: The third dimension in video studio work

The C I combines a tripod with a pneumatic central column. The air pressure inside the central column can be adjusted to suit the exact weight of your configuration, so the camera actually floats on a cushion of air. A brake locks the central column in any position, while a transport latch lets you carry the pedestal safely, even when the central column is under pressure. The maintenance-free central column rests on six ball bearings, two of which can be adjusted to ensure jerk-free motion even after long, intensive shoots. Each bearing is coated with hard rubber to absorb sliding noises.

Advantages of the C I:

- Air charging with pump
- Large height range and silent dolly movement
- column can be locked in place by brake at any height
- optimally adjustable air pressure to balance any camera configuration
- fast, fool-free set-up

Technical Facts

Recommended for	fluid heads FSB, DV 6, DV 8; DV 8/100, DV 10, DV 12, Video 15 (with #1030); Video 18
Weight	9.2 kg / 20.3 lbs
Payload	20 kg / 44.1 lbs
Height range	68 - 157 cm / 26.8 - 61.8 in
Lift	39 cm / 15.4 in
Clearance	93 cm / 36.6 in
Head fitting	flat base

Further photos



Order data

Article	Order code
Pedestal C I incl. Dolly DV 75, pump	4191

This product is also available in the following systems:

Article	Order code
---------	------------

Accessories



Cover ENG 2



Adapter Ped C
I/DV



Adapter Ped C
I/Plus

set your ideas in motion!