

CM-960 Agile Demodulator

Features:

- * Built-in CPU Control and Two-digit LED Display.
- * With AGC Circuit and SAW Filter
- * Last Channel Memory
- * TV (VHF.UHF) and CATV Bands Input Channels Available
- * Offer AC Power Outlet
- * MPX Output (Optional)

Specifications:

RF		VIDEO	
Input Frequency	NTSC :54~806MHz	Output Level	1.0Vp-p TYP Adjustable (75 ohm Load)
	PAL-D :48~870MHz	Frequency Response	
	PAL-B :46~870MHz	NTSC : 0~3.6 MHz, ± 1.5 dB	
Input Level	-5~+20 dBmV	PAL-D : 0~4.0 MHz, ±1.5 dB. 4.43~6 MHz, -3dB	
Noise Figure	10 dB (Max.)	PAL-B : 0~4.0 MHz, ±1.5 dB. 4.43~6 MHz, -3 dB	
Tuning Increment	NTSC : 62.5 KHz	D/G	NTSC : 6%
	PAL-D : 50.0 KHz		PAL-D : 5%
	PAL-B : 50.0 KHz		PAL-B : 5%
Image Rejection		D/P	2°
NTSC : VHF 50dB (Min.). UHF 50dB (Min.)		OTHERS	
PAL-D : VHF 50dB (Min.). UHF 50dB (Min.)		Power	115V AC/60Hz or 220V AC/50Hz
PAL-B : VHF 50dB (Min.). UHF 50dB (Min.)		Auxiliary AC Outlet	115V AC/600W or 220V AC/600W
AUDIO		Temperature Range	0~50°C
Output Level	500mVrms TYP Adjustable (600ohm Load)	Dimensions	481(W) x 135(D) x 44(H)mm
		Weight	2.0KGS
S/N Ratio	55 dB (Min.)	Packing	1 PC/Inner Box
MPX Output Level	500mVrms Adjustable (600ohm Load) (Optional)		9 PCS/22.0KGS/2.91'/CTN