

Specification

Input system:

Composite-Video/S-Video: NTSC3.58/NTSC4.43/PAL/PAL N/PAL M/SECAM auto detection

YCbCr: Component YCbCr interlaced video

PC: Passthrough

YPbPr: Passthrough

TV: PAL or SECAM local system dependance

Input Terminals

- Video Jacks

- Composite-Video: 1 Vp-p, RCA jack
- S-Video: 1 Vp-p, Cb/Cr: 0.7 Vp-p, RCA jack
- YCbCr: Y: 1Vp-p, Cb/Cr: 0.7 Vp-p, RCA jack x 3
- PC: R/G/B: 0.7 Vp-p, Pb/Pr: 0.7 Vp-p, RCA jack x 3
- YPbPr: Y: 1 Vp-p, Pb/Pr: 0.7 Vp-p, RCA jack x 3
- TV: Phono connector

- Audio jacks

- Composite-Video/S-Video Audio: RCA jack x 2
- YCbCr/YPbPr Audio: RCA jack x 2
- PC Audio: Phone jack x1

Output system:

- MHD-1P:

- **720x480@60Hz** for vertical sync 60Hz input source. Or for vertical sync 50Hz input source converted to 60 Hz.
- **720x576@50Hz** for vertical sync 50Hz input source.

- MHD-2P:

Output resolution	Size	Vert.(Hz)	Hori.(KHz)	Scan Mode
VGA	640x480	60	31.2	Progressive
		72	37.9	
		75	37.5	
		85	43.3	
SVGA	800x600	60	37.9	Progressive
		72	48.0	
		75	46.9	
		85	53.7	
XGA	1024x768	60	48.4	Progressive
		70	56.5	
		75	60.0	
WXGA	1280x768	60	48.4	Progressive
SXGA	1280x1024	60	64.0	Progressive
480p	852x480	60	31.5	Progressive
576p	852x576	50	31.2	Progressive
720p	1280x720	60	44.8	Progressive
1080i	1920x1080	60	33.6	Interlaced

Output Terminals:

- Video jacks: R/G/B: 0.7 Vp-p, H/V: 5 Vp-p, HD-15 Female connector
- Audio jacks: RCA jack x 2, Phone jack x1

Power Supply:

- AC to DC power adaptor: AC:120V, 50/60Hz, DC: 12V,800mA

Dimensions: 280(W)x195(D)x53(H)mm

Weight: 1.5kg

Accessorys:

- HD-15 to HD-15 VGA cable x 1, Remote X1
- Earphone cable x 1, AC power adaptor,
- RCA to RCA video cable x 1, AC power cable,
- 3RCA to 3RCA video cable x 1,
- S-Video input cable x 1,
- 2RCA x2RCA video cable x 1,