

# HM-S28G Series

Day & Night

1/3 " IR Color CCD Camera



The dual-glasses



Built-in double filter automatic switching device

## Product Feature

- With 1/3" Sony Super HAD color CCD sensor.
- The image resolution is including 420 TV lines and 480 TV lines.
- 0Lux(IR on). The lens have 4, 6, 8 (12mm Option )/ F2.0 fixed focal lens.
- With 28 units IR LED and could makes the picture bright and shining.
- In a suitable condition, the effective detection distance is 20M.
- With the glass separation (dual-glasses) could avoid the dirt and dust sticky on the glasses and caused the blur, atomization phenomenon and no clear appearance when IR starting.
- Built-in double filter automatic switching device (Option).
- The infrared electric circuit with the patent special arrangement design. When one damaged, does not affect other infrareds the normal movement.
- With the electronic shutter, the back light compensation(BLC), automatic gain control(AGC), white balanced locking in the automatic control function.
- No color-rolling design, colored image is clear, to specific target color saturated, the accuracy is high.
- By the most effective infrared arrangement, the picture nature clearly does not have the dead angle in the infrared projection scope, the effect is extremely good.
- The CDS is automatic starting, it could be all-weather 24 hours surveillance in 0Lux illumination.
- The top cover and the main-body cover use the most hardness aluminum alloy manufacture.
- It has through the IP68 waterproofing, CE \ FCC and RoHS certified



# HM-S28G Series

Day & Night

1/3" IR Color CCD Camera



## Specification

Model	HM-S28GN	HM-S28GP	HM-S28GNH	HM-S28GPH
Pick-Up Element	1/3" Sony Super HAD Color CCD sensor			
Number Of pixel	512(H)*492(V) <NTSC>	500(H)*582(V) <PAL>	768(H)*494(V) <NTSC>	752(H)*582(V) <PAL>
Resolution	420 TV lines		480 TV lines	
Min. Illumination	0.5Lux / F2.0 , 0Lux(20 meters IR ON)			
S/N Ratio	More than 48db (AGC off)			
Electronic Shutter	1/60 (1/50) to 1/100,000 sec			
Gamma	0.45			
Iris Mode	AES			
White Balance	ATW			
Video Output	1.0 Vp-p composite, 75Ω			
Lens	Standard 4,6,8mm(12mm option)			
BLC	Auto			
AGC	Auto			
IR LED	28units (850nm IR LED)			
I P	IP-68			
Storage Temperature	- 30°C ~60°C			
Operating Temperature	- 10°C ~50°C			
Power Source	DC 12V±10%			
Current Consumption	90mA(IR OFF)/350mA(IR ON)			
Weight	326g			
IR Cut	Option			

