

HM-Z50HQ Series

Day & Night

Adjustable Vari-Focal and Water Resistance IR Color CCD Camera



The dual-glasses



Waterproofing exterior adjustment vari-focal lens



The camera waterproofing setting box



The electric cable waterproofing nut is easy to construction

Product Feature



Built-in double filter automatic switching device

- With 1/3" Sony Super HAD color CCD sensor.
- The image resolution is 540 TV lines.
- Built-in automatic iris manual adjust zoom lens 4~9mm/F1.8 standard package, lens 9~22mm/F1.8 (option).
- With 56 units IR LED and could makes the picture bright and shining.
- In a suitable condition, the effective detection distance is 50M.
- (Innovation design) The waterproof exterior adjustment zoom lens, by the thread adjustment way to adjust Zoom & Focus, it makes pictures more clear and sharp.
- (Innovation design) In the camera waterproofing setting box, it sets the space for power source and the wiring and convenience construction.
- (Innovation design) The electric cable waterproofing nut, then completes by the simple tool, facilitates the construction.
- Built-in double filter automatic switching device.
- With the glass separation (dual-glasses) could avoid the dirt and dust sticky on the glasses and caused the blur, atomization phenomenon and no clear appearance when IR starting.
- The infrared electric circuit with the patent special arrangement design. When one damaged, does not affect other infrareds the normal movement.
- With the automatic gain control(AGC), the automatic white balanced(AWB) and the back light compensation(BLC) function.
- The top cover and the main-body cover use the most hardness aluminum alloy manufacture.
- It has through the IP68 waterproofing, CE、FCC and RoHS certified.



HM-Z50HQ Series

Day & Night

Adjustable Vari-Focal and Water Resistance IR Color CCD Camera



Specification

Model	HM-Z50HQ-NH	HM-Z50HQ-PH
Pick-Up Element	1/3" Sony Super HAD color CCD sensor	
Process	Sony HQ1 DSP Processor	
Number Of pixel	768(H)*494(V) <NTSC>	752(H)*582(V) <PAL>
Resolution	540 TV lines	
Min. Illumination	0.25Lux / F1.2 , 0Lux(50 meters IR ON)	
S/N Ratio	More than 52db (AGC off)	
Electronic Shutter	1/60 (1/50) to 1/100,000 sec	
Gamma	0.45	
Iris Mode	AI	
White Balance	ATW	
Video Output	1.0 Vp-p composite, 75Ω	
Lens	4~9mm/F1.8 DC Auto iris Lens(9~22mm/F1.8 DC Auto iris Lens option)	
BLC	Auto	
Gain Control	Auto	
Scan Mode	Interlace	
Synchronization	INT(internal)	
IR LED	56units (850nm IR LED)	
I P	IP-68	
Storage Temperature	- 30°C ~60°C	
Operating Temperature	- 10°C ~50°C	
Power Source	DC 12V±10%	
Current Consumption	190mA(IR OFF)/670mA(IR ON)	
Weight	1230g	
IR Cut	Yes(Built-in)	

