

Bullet CCD Camera

Bullet Camera



SPECIFICATIONS

Model	XB636
Image Pick-up Device	SHARP 1/4" Color CCD
Effective Picture Elements	NTSC: 510*492, PAL: 500*582 (H*V)
Horizontal Resolution	330 TV lines
Minimum Illumination	0.2 LUX @ F2.0
S/N Ratio	More than 48 dB
Auto Electronic Shutter	NTSC: 1/60s~1/100,000s, PAL: 1/50s~1/110,000s
Gain Control	Automatically
White Balance	Automatically (2500K~9500K)
Gamma Characteristic	0.45
Lens Furnished	Corn Lens 3.7 mm / F2.0
Synchronous System	Internal, Negative sync.
Video Output	1 Vp-p Composite Video / 75 Ohms
Power Supply	12V DC / 80 mA
Operating Temp.	-10°C to 50°C (14°F to 122°F)
Water Resistance	IP66
Dimensions	24mm (φ) * 70 mm (L)

Design and specifications are subject to change without notice.

FEATURES

- > Bullet color camera with SHARP 1/4" CCD sensor.
- > Employs Digital Signal Processor (DSP) chip-set for image control.
- > Pixel number: NTSC=270K / PAL=320K.
- > High sensitivity, low smear, high anti-blooming and high S/N ratio.
- > Build-in functions: Auto Electronic Shutter (AES), Auto Gain Control (AGC), Auto White Balance (AWB).
- > Built-in IR-cut optical filter.

DIMENSIONS

