# **Hidden Camera**

## Mini Case Camera





XS6A4 XS6B4

#### **FEATURES**

- > Color camera in metal case with SHARP 1/3" CCD sensor.
- Employs Digital Signal Processor (DSP) chip-set for image control.
- > Pixel number: NTSC=270K / PAL=320K (Normal Resolution). NTSC=380K / PAL=470K (High Resolution).
- > High sensitivity, low smear, high anti-blooming and high S/N ratio.
- > Build-in functions: Auto Electronic Shutter (AES), Auto Gain Control (AGC), Auto White Balance (AWB).
- > Small size (36x36) and furnished with DC power cable and video cable.
- > Built-in anti-aliasing and IR-cut optical filter.

### **SPECIFICATIONS**

Model	XS6A4	XS6B4
Image Pick-up Device	SHARP 1/3" CCD Normal Resolution	SHARP 1/3" CCD High Resolution
Effective Picture Elements	NTSC: 510*492, PAL: 500*582 (H*V)	NTSC: 768*494, PAL: 752*582 (H*V)
Horizontal Resolution	380 TV lines	470 TV lines
Minimum Illumination	0.1 LUX @ F2.0	
S/N Ratio	More than 48 dB	
Auto Electronic Shutter	NTSC: 1/60s~1/100,000s, PAL: 1/50s~1/110,000s	
Gamma Characteristic	0.45	
Lens Furnished	Board lens 3.6mm / F2.0	
Gain Control	Automatically	
White Balance	Automatically (2500K~9500K)	
Synchronous System	Negative sync. Internal	
Video Output	1 Vp-p Composite Video / 75 Ohms	
Power Supply	DC 12V / 80 mA	
Operating Temp.	-10°C to 50°C (14°F to 122°F)	
Dimensions	36 mm (L) * 36 mm (W) * 20 mm (H)	

Design and specifications are subject to change without notice.

## **DIMENSIONS**



