

B/W CCD Camera

Dome Camera



SPECIFICATIONS



Model	XD373	XD113
Image Pick-up Device	A1Pro 1/3" B/W CCD Normal Resolution	SONY 1/3" B/W CCD Normal Resolution
Effective Picture Elements	EIA: 510*492, CCIR: 500*582 (H*V)	EIA: 510*492, CCIR: 500*582 (H*V)
Horizontal Resolution	420 TV lines	420 TV lines
Minimum Illumination	0.2 LUX @ F2.0	0.1 LUX @ F2.0
S/N Ratio	More than 48dB	
Auto Electronic Shutter	EIA: 1/60s ~ 1/100,000s, CCIR: 1/50s ~ 1/110,000s	
Gain Control	Automatically	
Gamma Characteristic	0.45	
Lens Furnished	Board Lens 3.6 mm / F2.0	
Synchronous System	Internal, Negative sync.	
Video Output	1 Vp-p Composite Video / 75 Ohms	
Power Supply	12V DC / 110 mA	
Operating Temp.	-10°C to 50°C (14°F to 122°F)	
Dimensions	100 mm (Φ) X 60 mm (H)	
Audio Output (Option)	2 Vp-p / 50 Ohms. RCA connector	

Design and specifications are subject to change without notice.

FEATURES

- > B/W dome camera with 1/3" CCD sensor (XD373).
- > B/W dome camera with 1/3" SONY Super HAD CCD sensor (XD113).
- > Pixel number: EIA=270K / CCIR=320K.
- > High sensitivity, anti-blooming, and high S/N ratio.
- > Build-in functions: Auto Electronic Shutter (AES), Auto Gain Control (AGC).
- > Furnished with DC power cable and video cable.
- > DC type, low power consumption.

DIMENSIONS



CCD Camera

DVR

CCTV Lens

Accessories