sachtler





Top class for the finest productions

Classic film cameras are being increasingly replaced by high definition cameras in the area of movie production. Sachtler's fluid head Cine 75 HD is ideal for both types of production. The payload range of 4 to 75 kg / 9 to 165 lb also comes with a huge selection of accessories for the various cameras used with the head. And, of course, interfaces for a Front Box and viewfinder extension are standard accessories.

Technical Facts

Weight Payload

Sliding range - plate

Counterbalance

Grades of drag

Tilt range

Temperature range

Camera fitting

Tripod/Pedestal fitting

Pan bar(s)

Level

Batteries Level

11.9 kg / 26.2 lbs

4 - 75 kg / 9 - 165 lbs

120 mm / 4.7 in

in 24 steps

9 each horizontal and vertical + 0

+90/-609

-40 $^{\circ}$ to +60 $^{\circ}$ C / -40 to +140 $^{\circ}$ F

Touch & Go® Plate 35

150 mm bowl, integrated flat base fitting

1, telescopic, Type Movie self-illuminating Touch Bubble

3 x 625U or LR9

Payload

C.O.G.* min. kg/max.

75 / 3" 7.0 / 108.3 /

100 / 4" 6.1 / 94.1 /


125 / 5" 5.4 / 83.1 /


150 / 6" 4.8 / 74.5 /

175 / 7" 4.4 / 9.6 67.5 / 200 / 8" 4.0 / 8.8 61.6 /

250 / 3.4 / 7.5 52.6 /


300 / 3.0 / 6.5 45.8 /





Kameraplattform Gewicht (kg)
Counterbalance

Damping



Dimensions

Further photos



Order data

Article	Order code
Cine 75 HD Fluid head	7502

This product is also available in the following systems:

Article	Order code

System Cine 75 7525

Accessories



Case V/C 75



Front pan bar



Mitchell adapter plate



Mitchell adapter piece with locking knob



Cable clamp V/C 75



Adapter FB/150



Accessory adapter



Accessory adapter with clamping