

## TES-1332A Light Meter

### FEATURES:

- Spectral Sensitivity close to CIE photo pic Curve
- Cosine Angular corrected
- Analog output jack for recording TES-1332A
- Data Hold function



### SPECIFICATIONS:

<b>Display</b>	3 1/2 digit LCD
<b>Measuring Range</b>	20/200/2000/20000 Lux 200/2000/20000/200000 Lux (1332A) 20000 lux-reading x 10; 200000 lux-reading x 100
<b>Overrange Display</b>	Highest digit of (1) is displayed
<b>Resolution</b>	0.1 Lux(1332A)
<b>Accuracy</b>	+/- 3% rdg +/- 0.5% f.s.(<10,000 lux) +/- 4% rdg +/- 10dgts (>10,000 lux) (calibrated to standard incandescent lamp, 2856 K)
<b>Repeatability</b>	±2%
<b>Temperature Characteristics</b>	±0.1%°C
<b>Measuring Rate</b>	Approx. 2 times/sec.
<b>Recorder Output</b>	DC 2V/f.s. (full scale)
<b>Operating Temperature &amp; Humidity</b>	0 ° to 40°C (32°F to 104 °F) < 70% R.H.
<b>Power Source</b>	1 x 9V battery
<b>Dimensions</b>	100mm(L) x 60mm(W) x 27mm(H)
<b>Dimension</b>	135mm(L) x 72mm(W) x 33mm(H)
<b>Weight</b>	250g
<b>Accessories</b>	Carrying case, 9V battery & Instruction Manual