
2SK168

Silicon N-Channel Junction FET

HITACHI

Application

VHF Amplifier, Mixer, Local oscillator

Outline

TO-92 (2)



1. Gate
2. Source
3. Drain

Absolute Maximum Ratings (Ta = 25°C)

Item	Symbol	Ratings	Unit
Gate to drain voltage	V_{GDO}	-30	V
Gate to source voltage	V_{GSS}	-1	V
Gate current	I_G	10	mA
Drain current	I_D	20	mA
Channel power dissipation	Pch	200	mW
Channel temperature	Tch	150	°C
Storage temperature	Tstg	-55 to +150	°C


Electrical Characteristics (Ta = 25°C)

Item	Symbol	Min	Typ	Max	Unit	Test conditions
Gate to drain breakdown voltage	$V_{(BR)GDO}$	-30	—	—	V	$I_G = -100 \mu A, I_S = 0$
Gate cutoff current	I_{GSS}	—	—	-10	nA	$V_{GS} = -0.5 V, V_{DS} = 0$
Drain current	I_{DSS}^{*1}	4	—	20	mA	$V_{DS} = 5 V, V_{GS} = 0$
Gate to source cutoff voltage	$V_{GS(off)}$	—	—	-3.0	V	$V_{DS} = 5 V, I_D = 10 \mu A$
Forward transfer admittance	$ y_{fs} $	8	10	—	mS	$V_{DS} = 5 V, V_{GS} = 0, f = 1 \text{ kHz}$
Input capacitance	Ciss	—	6.8	—	pF	$V_{DS} = 5 V, V_{GS} = 0, f = 1 \text{ MHz}$
Reverse transfer capacitance	Crss	—	0.1	—	pF	$V_{DS} = 5 V, V_{GS} = 0, f = 1 \text{ MHz}$
Power gain	PG	—	27	—	dB	$V_{DS} = 5 V, V_{GS} = 0, f = 100 \text{ MHz}$
Noise figure	NF	—	1.7	—	dB	$V_{DS} = 5 V, V_{GS} = 0, f = 100 \text{ MHz}$


Note: 1. The 2SK168 is grouped by I_{DSS} as follows.

D	E	F
4 to 8	6 to 12	10 to 20


Maximum Channel Power Dissipation Curve




Typical Output Characteristics (1)











Typical Output Characteristics (2)




Typical Transfer Characteristics









Input and Output Admittance vs. Frequency




Transfer Admittance vs. Frequency




Input and Output Admittance vs. Drain Current



Transfer Admittance vs. Drain Current




Power Gain and Noise Figure
Test Circuit



C₁, C₂ : 0 to 30 pF Variable Air

L₁ : 3.5 T 1 mmφ Copper Ribbon, Tin plated 10 mm Inside dia.

L₂ : 4.5 T 1 mmφ Copper Ribbon, Tin plated 10 mm Inside dia.



Hitachi Code	TO-92 (2)
JEDEC	Conforms
EIAJ	Conforms
Weight (reference value)	0.25 g

Cautions

1. Hitachi neither warrants nor grants licenses of any rights of Hitachi's or any third party's patent, copyright, trademark, or other intellectual property rights for information contained in this document. Hitachi bears no responsibility for problems that may arise with third party's rights, including intellectual property rights, in connection with use of the information contained in this document.
2. Products and product specifications may be subject to change without notice. Confirm that you have received the latest product standards or specifications before final design, purchase or use.
3. Hitachi makes every attempt to ensure that its products are of high quality and reliability. However, contact Hitachi's sales office before using the product in an application that demands especially high quality and reliability or where its failure or malfunction may directly threaten human life or cause risk of bodily injury, such as aerospace, aeronautics, nuclear power, combustion control, transportation, traffic, safety equipment or medical equipment for life support.
4. Design your application so that the product is used within the ranges guaranteed by Hitachi particularly for maximum rating, operating supply voltage range, heat radiation characteristics, installation conditions and other characteristics. Hitachi bears no responsibility for failure or damage when used beyond the guaranteed ranges. Even within the guaranteed ranges, consider normally foreseeable failure rates or failure modes in semiconductor devices and employ systemic measures such as fail-safes, so that the equipment incorporating Hitachi product does not cause bodily injury, fire or other consequential damage due to operation of the Hitachi product.
5. This product is not designed to be radiation resistant.
6. No one is permitted to reproduce or duplicate, in any form, the whole or part of this document without written approval from Hitachi.
7. Contact Hitachi's sales office for any questions regarding this document or Hitachi semiconductor products.

HITACHI

Hitachi, Ltd.

Semiconductor & Integrated Circuits.
Nippon Bldg., 2-6-2, Ohte-machi, Chiyoda-ku, Tokyo 100-0004, Japan
Tel: Tokyo (03) 3270-2111 Fax: (03) 3270-5109

URL North America : <http://semiconductor.hitachi.com/>
Europe : <http://www.hitachi-eu.com/hel/ecg>
Asia (Singapore) : <http://www.has.hitachi.com.sg/grp3/sicd/index.htm>
Asia (Taiwan) : http://www.hitachi.com.tw/E/Product/SICD_Frame.htm
Asia (HongKong) : <http://www.hitachi.com.hk/eng/bo/grp3/index.htm>
Japan : <http://www.hitachi.co.jp/Sicd/indx.htm>

For further information write to:

Hitachi Semiconductor
(America) Inc.
179 East Tasman Drive,
San Jose, CA 95134
Tel: <1> (408) 433-1990
Fax: <1> (408) 433-0223

Hitachi Europe GmbH
Electronic components Group
Dornacher Straße 3
D-85622 Feldkirchen, Munich
Germany
Tel: <49> (89) 9 9180-0
Fax: <49> (89) 9 29 30 00

Hitachi Europe Ltd.
Electronic Components Group.
Whitebrook Park
Lower Cookham Road
Maidenhead
Berkshire SL6 8YA, United Kingdom
Tel: <44> (1628) 585000
Fax: <44> (1628) 778322

Hitachi Asia Pte. Ltd.
16 Collyer Quay #20-00
Hitachi Tower
Singapore 049318
Tel: 535-2100
Fax: 535-1533

Hitachi Asia Ltd.
Taipei Branch Office
3F, Hung Kuo Building, No.167,
Tun-Hwa North Road, Taipei (105)
Tel: <886> (2) 2718-3666
Fax: <886> (2) 2718-8180

Hitachi Asia (Hong Kong) Ltd.
Group III (Electronic Components)
7/F., North Tower, World Finance Centre,
Harbour City, Canton Road, Tsim Sha Tsui,
Kowloon, Hong Kong
Tel: <852> (2) 735 9218
Fax: <852> (2) 730 0281
Telex: 40815 HITEC HX

Copyright ' Hitachi, Ltd., 1999. All rights reserved. Printed in Japan.

HITACHI