

Victor 88E Specifications		
Basic Function	Range	Basic accuracy
DC Voltage	200mV/2V/20V/200V/1000V	±(0.5%+4)
	400mV/4V/40V/400V/1000V	
DC Voltage	40mV/400mV	±(0.5%+4)
AC Voltage	2V/20V/200V/750V	±(0.8%+6)
	400mV/4V/40V/400V/750V	
AC Voltage	40mV/400mV	±(1.6%+6)
DC Current	200uA/2mA/ 20mA/200mA/20A	±(1.0%+10)
	400uA/4mA/40mA/400mA/20A	
AC Current	20mA/200mA/20A	±(1.5%+5)
	400uA/4mA/40mA/400mA/20A	
Resistance	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/200MΩ	±(0.8%+4)
	400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ	
Capacitance	20nF/2uF/200uF	±(2.5%+8)
	40nF/400nF/4uF/40uF/200uF	
Frequency	20kHz/200kHz	±(0.5%+4)
	100Hz/1000Hz/10kHz/100kHz/1MHz/30MHz	
Celsius	(-40~1000)°C	±(1.0%+4)
Fahrenheit	(0~1832)°F	±(0.8%+5)

Special Function	
Diode test	√
Continuity buzzer	√
Low battery indication	√
Relative value measurement	√
Max./Min.Value selection	√
Backlight	
Data Hold	√
Auto power off	√
Backlight	√
Function protection	√
Restorable Fuse protection	√
Shock proof protection	√
Input impedance	10MΩ
Sampling rate	3 times/s
AC Frequency response	40~400Hz
Operation way	Manual range
Max. Display	3999
LCD size	65×45mm
Battery	3V(1.5V×2)

Product color	Case: dark gray; Holster color: yellow
Product Net Weight	Approx:400g
Product Dimension	189×97×35mm