

Victor 88D Specifications		
Basic Function	Range	Basic accuracy
DC Voltage	200mV/2V/20V/200V/1000V	±(0.1%+5)
	400mV/4V/40V/400V/1000V	
DC Voltage	40mV/400mV	
AC Voltage	2V/20V/200V/750V	±(0.8%+25)
	400mV/4V/40V/400V/750V	
AC Voltage	40mV/400mV	
DC Current	200uA/2mA/ 20mA/200mA/20A	±(0.5%+4)
	400uA/4mA/40mA/400mA/20A	
AC Current	20mA/200mA/20A	±(1.5%+25)
	400uA/4mA/40mA/400mA/20A	
Resistance	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/200MΩ	±(0.4%+5)
	400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ	
Capacitance	20nF/2uF/200uF	±(3.5%+10)
	40nF/400nF/4uF/40uF/200uF	
Frequency	20kHz/200kHz	±(3.0%+150)
	100Hz/1000Hz/10kHz/100kHz/1MHz/30MHz	
Celsius	(-40~1000)°C	±(0.8%+40)
Fahrenheit	(0~1832)°F	

Special Function	
Diode test	√
Continuity buzzer	√
Low battery indication	√
Relative value measurement	
Max./Min.Value selection	
Backlight	√
Data Hold	
Auto power off	√
Backlight	
Function protection	√
Restorable Fuse protection	√
Shock proof protection	√
Input impedance	10MΩ
Sampling rate	3 times/s
AC Frequency response	40~400Hz
Operation way	Manual range
Max. Display	19999
LCD size	65×45mm
Battery	9V(6F22)

Product color	Case: dark gray; Holster color: yellow
Product Net Weight	Approx:400g
Product Dimension	189×97×35mm