

Victor 88B Specifications		
Basic Function	Range	Basic accuracy
DC Voltage	200mV/2V/20V/200V/1000V	±(0.5%+3)
AC Voltage	2V/20V/200V/750V	±(0.8%+5)
	200mV/2V/20V/200V/750V	
DC Current	20uA/200uA/20mA/200mA/2A/20A	
	20mA/200mA/20A	±(0.8%+4)
	2mA/20mA/200mA/20A	
AC Current	200mA/2A/20A	
	20mA/200mA/20A	±(1.0%+5)
	2mA/20mA/200mA/20A	
Resistance	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/200MΩ	±(0.8%+3)
	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ/2000MΩ	
Capacitance	20nF/2uF/200uF	±(2.5%+20)
	20nF/200nF/2uF/20uF/200uF	
Frequency	2kHz/200kHz	±(3.0%+15)
	2kHz/20kHz/200kHz/2000kHz/10MHz	
Inductance	2mH/20mH/200mH/2H/20H	
Celsius	(-40~1000)°C	±(1.0%+3)

Special Function	
Diode test	√
Continuity buzzer	√
Low battery indication	√
Data Hold	√
Auto power off	√
Backlight	√
Function protection	√
Restorable Fuse protection	√
Shock proof protection	√
Input impedance	10MΩ
Sampling rate	3 times/s
AC Frequency response	40~400Hz
Operation way	Manual range
Max. Display	1999
LCD size	65×45mm
Battery	9V(6F22)

Product color	Case: dark gray; Holster color: yellow
Product Net Weight	Approx: 400g
Product Dimension	189×97×35mm