

VICTOR 81D Technical data		
Basic Function	Range	Basic accuracy
DC Voltage	400mV/4V/40V/400V/600V	±(0.5%+4)
AC Voltage	400mV/4V/40V/400V/600V	±(0.8%+6)
DC Current	400uA/4000uA/40mA/400mA/10A	±(1.0%+10)
AC Current	400uA/4000uA/40mA/400mA/10A	±(1.5%+10)
Resistance	400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ	±(0.8%+4)
Capacitance	4nF/40nF/400nF/4uF/40uF/100uF	±(3.5%+8)
Frequency	1Hz/10Hz/100Hz/1kHz/10kHz/100kHz/30MHz	±(0.5%+10)
Celsius	-20-1000°C	±(1.0%+5)

Special Function	
Diode test&Continuity buzzer	√
Low battery indication	√
Data hold	√
Auto power off	√
Function protection	√
10A fuse	√
Shockproof protection	√
self-resume fuse protection for mA	√
Unit symbol display	√
Relative value measurement	√
Duty cycle measurement	0.1%-99.9%
Input impedance	10MΩ
Sampling rate	3 times/s
AC Frequency response	(40-400)Hz
Operation way	Auto range
Max.Display	3 3/4 (3999)
LCD size	57×33mm
Battery	3V(1.5×2)

General Characters	
Product color	Case: dark gray; Holster color: yellow
Product Net Weight	Approx: 200g (including battery)
Product Dimension	145×80×30mm