

Victor 89A Specifications		
Basic Function	Range	Basic accuracy
DC Voltage	200mV/2V/20V/200V/1000V	±(0.5%+3)
AC Voltage	20V/200V/750V	±(0.8%+5)
DC Current	200mV/2V/20V/200V/750V	
AC Current	2mA/200mA/20A	±(1.5%+3)
	20mA/200mA//20A	
	200uA/2000uA/20mA/200mA/20A	
Resistance	20mA/200mA /20A	±(1.5%+5)
	200mA/20A	
	200uA/2000uA /20mA/200mA/20A	
	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/200MΩ	±(0.8%+3)
	200Ω/2kΩ/20kΩ/200kΩ/20MΩ/200MΩ	
	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ	
Capacitance	20nF/2uF/200uF	±(2.5%+20)
Celsius	(-40~1000)°C	
Fahrenheit	(0~1832)°F	

Special Function	
Diode test	√
Continuity buzzer	√
Low battery indication	√
Data Hold	√
Auto power off	√
Function protection	√
Restorable Fuse protection	√
Shock proof protection	√
Input impedance	10MΩ
Sampling rate	3 times/s
AC Frequency response	40~400Hz
Operation way	Manual range
Max. Display	1999
LCD size	61×36mm
Battery	9V(6F22)

Product color	Case: dark gray; Holster color: yellow
Product Net Weight	Approx: 270g
Product Dimension	155×90×48mm