

Specification	Range	Accuracy
DC Voltage	400mV/4V/40V/400V	±(0.5%+4)
	1000V	±(1.0%+6)
AC Voltage	4V/40V/400V	±(0.8%+10)
	750V	±(1.0%+10)
AC Current	40A/400A/1000A	±(2.5%+8)
DC Current	40A/400A/1000A	±(2.5%+8)
Resistance	400Ω	±(0.8%+5)
	4kΩ/40kΩ/400kΩ/4MΩ	±(0.8%+4)
	40MΩ	±(1.2%+10)
Capacitance	10nF/100nF/1uF/10uF/100uF	±(3.0%+10)
	1000uF	±(5.0%+10)
Frequency	9.999Hz/99.99Hz/999.9Hz/9.999kHz/99.99kHz/999.9kHz	±(0.5%+4)
Features		
Diode, Continuity Test	√	
Continuity Test	√	
Low Voltage Display	√	
True RMS	√	
Unit Symbol Display	√	
Data Hold	√	
Auto Power Off	√	
Overload Protection	√	
Input Impedance	10MΩ	
Sampling Rate	3 times/s	
AC Current Response	(50-60)Hz	
Operation Way	Auto Range	
Max. Display	3999	
Jaw Size	38mm	
General Information		
Power	9V (6F22)	
Product Color	Case: black; Holster: orange	
Product Weight	Approx.270g	
Product Size	225x76x32mm	