

Specification	Range	Accuracy
DC Voltage	400mV/4V/40V/400V	±(0.5%+4)
	1000V	±(1.0%+6)
AC Voltage	400mV	±(1.6%+8)
	4V/40V/400V	±(0.8%+10)
	750V	±(1.0%+10)
AC Current	40A/400A/1000A	±(2.5%+8)
DC Current	40A/400A/1000A	±(2.5%+8)
Resistance	400Ω	±(0.8%+5)
	4kΩ/40kΩ/400kΩ/4MΩ	±(0.8%+4)
	40MΩ	±(1.2%+10)
Capacitance	4nF	±(3.5%+30)
	40nF/400nF/4uF/40uF	±(3.0%+10)
	100uF	±(5.0%+10)
Frequency	9.999Hz/99.99Hz/999.9Hz/9.999kHz/99.99kHz	±(0.5%+4)
Features		
Diode / Continuity Test	√	
Continuity Test	√	
Low Voltage Indication	√	
Unit Symbol Display	√	
Data Hold	√	
Auto Power Off	√	
Overload Protection	√	
Sampling Rate	3 times/s	
AC Current Response	(50-60)Hz	
Operation Way	Auto Range	
Max. Display	3999	
Jaw Size	55mm	
General Information		
Power	9V (6F22)	
Product Color	Black +Orange	
Product Weight	410g	
Product Size	257x82x40mm	