

Specification	Range	Best Accuracy
DC Voltage	400mV/4V/40V/400V	±(0.5%+4)
	1000V	±(1.0%+6)
AC Voltage	400mV	±(1.6%+8)
	4V/40V/400V	±(0.8%+10)
	750V	±(1.0%+10)
DC Current	400A	±(2.5%+20)
	2000A	±(3.5%+20)
AC Current	400A	±(2.5%+20)
	2000A	±(3%+10)
Resistance	400Ω	±(0.8%+5)
	4kΩ/40kΩ/400kΩ/4MΩ	±(0.8%+4)
	40MΩ	±(1.2%+10)
Capacitance	40nF	±(5.0%+30)
	400nF/4μF/40μF	±(3.5%+8)
	100μF	±(5.0%+10)
Frequency	5.120Hz/51.20Hz/512.0Hz/5.120kHz/51.20kHz/512.0kHz/100.0kHz	±(0.5%+4d)
<b>Features</b>		
Diode/Continuity Test	√	
Relative Values	√	
Low battery indication	√	
Data Hold	√	
Duty Cycle	√	
Auto power off	√	
Relative Value Measurement	√	
Sampling rate	3 times/s	
AC frequency response	50/60Hz	
Operation way	Auto Range	
Max. Display	3999	
Jaw Size	55mm	
<b>General Information</b>		
Power Supply	9V(6F22)	
Product Weight	About 565g	
Product Size	275x96x50mm	