

Specification	Range	Basic Accuracy
DC Voltage	400mA/4V/40V/400V	±(0.5%+4)
	600V	±(1.0%+6)
AC Voltage	4V/40V/400V/600V	±(0.8%+10)
	600V	±(1.0%+10)
DC Current	40A/600A	±(3%+10d)
AC Current	40A/600A	±(3%+8d)
Resistance	400Ω	±(0.8%+5)
	4kΩ/40kΩ/400kΩ/4MΩ	±(0.8%+4)
	40MΩ	±(1.2%+10)
Capacitance	4nF	±(3.5%+30)
	40nF/400nF/4uF/40uF	±(3.0%+10d)
	100uF	±(5.0%+10d)
Frequency	9.999Hz/99.99Hz/999.9Hz/9.999kHz/99.99kHz	±(0.5%+4)
Temperature	(-20~400)°C	±(1.0%+5)
	(400~1000)°C	±(1.5%+15)
Features		
Diode, Continuity Test	√	
Continuity Test	√	
Low Voltage Display	√	
Relative Values	√	
Unit Symbol Display	√	
Data Hold	√	
Auto Power Off	√	
Overload Protection	√	
Input Impedance	10MΩ	
Sampling Rate	3 times/s	
AC Current Response	(50-60)Hz	
Operation Way	Auto Range	
Max. Display	3999	
Jaw Size	35mm	
General Information		
Power	9V (6F22)	
Product Color	Case: black; Holster: orange	
Product Weight	Approx.258g	
Product Size	210x73x39mm	