## Component Video & Digital Audio/IR CAT5 Extender

ITEM NO.: YE01D



The Component Video & Digital audio BALUN is designed for component video signal (Y, Pb, Pr) and one digital audio or IR signal be transmitted via cost effective one CAT5 UTP cable. Used in pairs, the Component Video/Digital Audio BALUN supports 480i/480p/720p/1080i/1080p video formats for hidefinition (HDTV) video application. Application for control rooms, multimedia rooms, communications centers, convention facilities, classroom video corporate projection system.

## YE01D Component Video (YPbPr) & Digital Audio/IR CAT5 Extender

- Designed for Component video and Digital Audio or IR pass through over one CAT5 UTP cable.
- Passive device, no power need.
- Up to 300 meters for video and 180 meters for Digital audio.
- Support up to HDTV. ( 480i /480p/720p/1080i/1080p)
- Perfect for DVD, VCR, DVR, TV, Satellite receivers, monitors, home theatre and other equipments supporting component video

## **Installation View: Using SPDIF Transmission** IR/Audio switch Component video source 0 (0)-Video/Digital audio Link Cable Y/Pb/P Y/Pb/Pr (O)3 (O) a (O) (O)\* SPDIF SPDIF **O O**! (WINE-Amplifier YE01D YE01D **Using IR Transmission** IR/Audio switch set to IR Component video source 0 (()-Y/Pb/Pr Y/Pb/Pr () (i) ٥đ ((); 0, **0** (O) YE01D YE01D IR emitter IR control module and IR sensor **Panel View:** LINK CABLE -SELECT

**Specification:** 

ITEM NO.	YE01D
Video Input	RCA x 3 : Y (75Ω · 1.0 Vp-p) · Pb Pr (75Ω · 0.7 Vp-p)
Audio Input	RCA x1
IR Pass through	2 pin removable terminal
Support Resolution	480i /480p/720p/1080i/1080p
Bandwidth	Video: 60Mz, 3dB roll off, Digital Audio: 25MHz, 1dB roll off
Link Connector	RJ45 x 1
Distance	Video:1080p at 50m,480i at 300m SPDIF:180M
CABLE FOR RJ45	Twisted Pair CAT 5 (AWG24)
Temperature	Operation: 0 to 55°C, Storage: -20 TO 85°C, Humidity: up to 95%
Dimensions mm	110 x 82 x 26



Weight g RoHS (FE C

Rev. B