



# SG15L / SG17L / SG19L CCTV LED Monitor



## Product Features

- 15" / 17" / 19" CCTV LED Monitor
- Various Video Connectors (BNC / VGA / S-Video)
- Support Multiple Language selections
- VESA Bracket Optional for Wall mount

## Specification

Specification \ Model		SG15L	SG17L	SG19L
DISPLAY	Screen Size	15" LED Backlight	17" LED Backlight	19" LED Backlight
	Aspect Ratio	4:3	5:4	5:4
	Max. Resolution	1024 x 768	1280 x 1024	1280 x 1024
	Viewable Size (HxV)	304.128 x 228.096 mm	337.92 x 270.336 mm	376.32 x 301.056 mm
	Pixel Pitch (HxV)	0.297 x 0.297 mm	0.264 x 0.264 mm	0.294 x 0.294 mm
	Brightness	300 cd/m <sup>2</sup>	250 cd/m <sup>2</sup>	250 cd/m <sup>2</sup>
	Contrast Ratio	700 : 1	1000 : 1	1000 : 1
	Viewing Angle (HxV)	140° / 125°	160° / 160°	170° / 170°
	Display Color	16.2M	16.7M	16.7M
	Response Time (Tr/Tf)	12 ms	5 ms	5 ms
	Panel Life Time	30,000 hrs		
I/O INTERFACE	Video Input	VGA (15pin D-SUB) x 1, BNC x 1, S-Video x 1		
	Video Output	BNC x 1		
	Audio Input	PC Audio in x 1, RCA Audio x 1		
	Audio Output	1W Speaker x 2, RCA Audio x 1		
ELECTRICAL	Power Input	AC 100 - 240V, 50/60Hz		
	Power Supply	DC12V / 3.5A		
GENERAL	Operating Condition	Temp.: 0°C to 50°C, Hum.: 20% ~ 80%		
	Storage Condition	Temp.: -20°C to 60°C, Hum.: 10% ~ 80%		
	Dimension (WxHxD)	355 x 340 x 285 mm	370 x 355 x 147 mm	420 x 408 x 147 mm
	Net Weight	2.3 kg	2.9 kg	4.3 kg
	Regulations	CE, FCC		
FEATURES	Built in Speakers	1W x 2		
	3D Comb Filter	-		
	3D De-interlace	-		
	OSD Languages	English, French, Russian, German, Chinese-Traditional, Spanish, Italian		
OPTION	Glass	Anti-Reflection Strengthened Glass		
	Mounts	DW1700C, DW1710C (12 kg Max. Weight)		

## Interface:

### Back View



### Front View



\*Specifications subject to change without notice. V1.0