

SPECIFICATIONS

MODEL	T121-IP	T156-IP	T215-IP	T240-IP
LCD Panel	12.1"	15.6"	21.5"	24"
Viewable Area (H/V-mm)	345.76 x 184.32	344.2 x 193.5	476.6 x 268.1	531.3 x 298.8
Profile Ratio	4 : 3	16 : 9	16 : 9	16:9
Max. Resolution (H/V)	1024 x 768	1920 x 1080	1920 x 1080	1920 x 1080
Pixel dot pitch (mm)	0.297 x 0.297	0.252 x 0.252	0.248x0.248	0.2767 x 0.2767
Display Colors	16.2M	262K	16.7M	16.7M
Brightness (nit)	500 [LED]	250 [LED]	250 [LED]	250 [LED]
Contrast Ratio	700:1	600:1	1000:1	1000:1
Response Time (Tr/Tf-ms)	3/5 ms	3/8 ms	1.3/3.7 ms	3.5 / 1.5 ms
Viewing Angle (U/D/L/R)	80 / 80 / 80 / 80	60 / 60 / 70 / 70	80 / 80 / 85 / 85	80 / 80 / 85 / 85
Dimensions (WxHxD) mm	299.6 x 238.9 x 61.8	401.5 x 251 x 60.3	532.3 x 323.3 x 65	575.9 x 347.8 x 56.7
Weight	2.3kg	3.4kg	5.4kg	5.8kg
Operating temperature	0° to 40° C			

12.1"



15.6"



21.5"



24"



SPECIFICATIONS

MODEL	T270-IP	T320-IP	T420-IP	T460-IP
LCD Panel	27"	31.5"	42"	46"
Viewable Area (H/V-mm)	697.6 x 336.15	698.4 x 392.85	930 x 523.26	1018.08 x 572.67
Profile Ratio	16:9	16:9	16:9	16:9
Max. Resolution (H/V)	1920 x 1080	1920 x 1080	1920 x 1080	1920 x 1080
Pixel dot pitch (mm)	0.31125 x 0.31125	0.36375 x 0.316375	0.4845 x 0.4845	0.53025 x 0.53025
Display Colors	16.7M	16.7M	16.7M	1073.7M
Brightness (nit)	300 [LED]	350 [LED]	350 [LED]	500 [LED]
Contrast Ratio	5000:1	3000:1	3000:1	4000:1
Response Time (Tr/Tf-ms)	7 / 5 ms	8 (G to G)	6.5 (G to G)	6.5 ms
Viewing Angle (U/D/L/R)	89 / 89 / 89 / 89	89 / 89 / 89 / 89	89 / 89 / 89 / 89	89 / 89 / 89 / 89
Dimensions (WxHxD) mm	658 x 396 x 60.5	761.6 x 455.2 x 75	994.6 x 587.2 x 81	1081.05 x 635.45 x 80.5
Weight	7kg	13kg	23kg	25kg
Operating temperature	0° to 40° C			

27"



32"



42"



46"



FEATURE

- Easy To Setup. Simply Use Mouse To Operate.
- No PC Required. Instant Connection To Display Image.
- Support ONVIF / IP Camera Live Display.
- Graphic User Interface (GUI).
- Aluminum panel Frame. Metal Case.
- Friendly OSD Function Controls.
- Full HD 1920 x 1080 High Resolution (1CH) / 720P (4CH).
- 12.1"~46" Full HD Available.
- VESA Standard Bracket.

SPECIFICATIONS

Operating System	Embedded LINUX operating system	
Image Code Control	Adjustable; variable bit stream and constant bit stream optional	
Dual Stream	Each channel can set main stream and sub stream	
Video Standard	1080P(1920x1080)30fps/ 960P((1280x960)/ 720P(1280x720)30fps	
Monitoring Image Quality	1080P(1920x1080)/ 960P((1280x960)/ 720P(1280x720)	
External Ports	Video Input	① 4x(1280*720) +sub[960*576]+1Ref.+4Play 4ch 720P IP Cameras ② 4x(1920*1080) +sub[960*576]+4Ref.+1Play 1ch 1080P IP Cameras
	Audio Input	2CH RCA
	Digital Input	1CH VGA + 1CH HDMI +1CH DVI
	Network Port	1 RJ45, 10M/100M self-adaptive LAN port
	USB Port	2 x USB 2.0 port
	HDD Port	E-SATA/(option)

INTERFACE

