

Max. distance via high quality 75Ω Coaxial Cable (Belden 1505A,1694A RG6U Testing)	From SDI source	To SDI monitor
SD resolution (270Mbps: 480i,576i)	400M	400M
HD resolution (1.45Gbps: 720p,1080i,1080p@24/25/30Hz)	200M	200M
Full HD resolution (2.97Gbps: 1080p@50/60Hz)	100M	100M
Max. distance via high quality 75Ω Coaxial Cable (Belden 1505A RG59 Testing)	From SDI source	To SDI monitor
SD resolution (270Mbps: 480i,576i)	300M	300M
HD resolution (1.45Gbps: 720p,1080i,1080p@24/25/30Hz)	150M	150M
Full HD resolution (2.97Gbps: 1080p@50/60Hz)	80M	80M

ITEM NO.	SR02E
SDI Standard Protocol	SMPTE 259M - SDI(270 Mbps) SMPTE 292M - HD-SDI(1.485 Gbps) SMPTE 424M - 3G-SDI(2.97 Gbps)
Output/ Input Connector	BNC x 3 (75Ω)
Power Supply	DC 5V 1A
Power Consumption	500 mA (Max)
Temperature	Operation: 0 to 55°C, Storage: -20 to 85°C, Humidity: up to 95%
Dimensions	48.7 x 140.3 x 25.2mm
Weight	160g