

RP-91/RP-92/RP-93 TEST LEAD


● FEATURES & SPECIFICATIONS:

<p>RP-91</p>	<ul style="list-style-type: none"> • Using On Bench Type LCR Meter. • Compatible On All Brands Bench Type LCR Meter. • 4-Wire Leads Compensate Internal Impedance Error.
<p>RP-92</p>	<ul style="list-style-type: none"> • High shield rate, low noise design, It remains steady and measurable even the capacitor which is lower than 1pF. • It supports multiple accessories to suit for different components. The probe tip can be replaced to extend the life of the product. • It is high efficiency and cost effective. • Cable Length: Approx. 0.8Meter (from connector to probe tip). • Terminal connection: BNC, 4 terminal-pair.
<p>RP-93</p>	<ul style="list-style-type: none"> • Low resistance 4 wire terminal-pair probe. • Compatible on all brands Milli-Ohm meter which input through Banana-Jacket. • High shield co-axis wire, low noise design. • Output 1A will not case to heating. • Gold plate alligator plug, low connect resistance, low corrosive. • 130 cm length, 90 grms weight.

RP-91/RP-92 APPLICATION



LCR-900
High Precision LCR Meter



RP-91
(for DIP Type parts)



RP-92
(for SMT type parts)

RP-93 APPLICATION



MR-30 DC Milliohm Meter



RP-93
(for resistance test)

SALES AGENT