

<b>Model Name</b>	<b>HS-2850</b>
<b>Product Name</b>	<b>HD/SD 12-Channel Portable Video Studio</b>
<b>Video Standard</b>	HD & SD
<b>Video Format</b>	3G/HD/SD input: 1080i 50/59.94/60Hz 1080p 25/30/59.94/60Hz HD Output: 1080i 50/59.94/60Hz SD: 576i 50Hz, 480i 59.94Hz
<b>Input Rutable / Crosspoint</b>	All 12, repeatable
<b>Video Input</b>	Standard: 8x SDI, 2x HDMI Max: 12x SDI, 3x HDMI
<b>Computer Graphic Interface</b>	Max 3 via HDMI
<b>Down-converted output</b>	2x SDI
<b>Video output</b>	3x SDI assignable: PGM, PVW, AUX & Clean Out 1x HDMI assignable: PGM & multi-view
<b>Audio input</b>	4x Balanced XLR
<b>Audio output</b>	2x Balanced XLR
<b>Embedded audio support</b>	Input up to 16 channels, Output 4 channels
<b>Audio Delay Calibration</b>	Up to 8 frames
<b>A+V switching</b>	Yes
<b>USK</b>	N/A
<b>DSK</b>	2x DSK support Lumakey & Linear key (Key / Fill)
<b>Picture in Picture</b>	2
<b>Logo Insertion</b>	2 (or 1 logo + 1 clock)
<b>Built-in Audio Mixer</b>	N/A
<b>Built-in Monitor Display</b>	17.3" HD TFT LED backlit, 1600x900 pix
<b>Built-in Intercom &amp; Tally</b>	8 channels (4 belt-packs incl.)
<b>Dimension (LxWxH)</b>	455 x 355 x 134 mm
<b>Weight</b>	19.6 Lbs (9 Kg), Reinforce Plastic Case
<b>Accessory</b>	CB-22H/23H/46/47/50