

IP PTZ Camera

30X, WDR, 1080P

DMC-20SEW

Picture



Feature

- 1/3" Panasonic PS-CMOS
- 2Megapixel IP PTZ Camera
- Optical 30x Zoom, Digital 32x Zoom, Auto Focus, Day & Night with ICR
- Low up to 0.003Lux with DSS(x32)
- WDR(120dB),DNR, Motion, Privacy Masking
- Preset(250), Group(12), Tour, Trace, Alarm(4/1)
- Outdoor Type(IP66), Dehumidification, Fan/Heater
- High Performance Streaming (Max. 30fps live view@1920x1080)

MODEL	DMC-20SEW
Video	
Image Sensor	1/3" 2Mega Panasonic CMOS
Scan mode	Progressive Scan
Total number of pixels	2010(H) × 1108 (V)
Number of active pixels	1944(H) × 1092 (V)
Resolution	1080p
Minimum illumination	Color : 0.5Lux , BW : 0.1Lux Min. 0.003Lux with DSS(32x)
S/N Ratio	50dB
Lens	
Lens	4.3~129mm(F1.6~F4.7) Optical(30x), Digital Zoom(32x), Total Zoom (960x)
Focus mode	Auto / Manual / Oneshot
Angle of view	D:71.3°~2.58°, H:58.9°~2.11°, V:45.3°~1.61°
Network	
Hardware	Flash (32Mbyte), RAM (256Mbyte) Ethernet:RJ-45(10/100BASE-T)
Video Output	Channel 1ch (CVBS) Compression H.264 & MJPEG Dual Codec FULL HD(1920X1080),HD(1280X720P), VGA(640X480),QVGA(320X240) Max. Frame rate 30/25 fps Bitrate control : CBR or VBR(64K~12Mbps)
Audio	Audio In(1), Audio Out(1),8 bit PCM (G711 u-law) 8Khz, Mono
Memory Slot	SD/SDHC Memory Slot/Max.32GB
Event	Alarm / Motion Detection : E-mail, FTP, Event, Noti- Service
Recording	Manual / Schedule / motion Detection / Sensor Event
Client Viewer	Web viewer, CMS, Max-i
Network Protocol	HTTP, TCP/IP, UDP, ARP, RARP, ICMP, RTP/RTSP/ DHCP, Telnet, FTP, ,NTP, DDNS, SMTP, UPNP, PPPoE, Onvif, PSIA
Pan/ Tilt	
Pan/Tilt angle	360° Endless / 92°
Pan Speed	0.1° ~ 240°/sec (64 Levels), Preset: 360°/sec
Preset point	250 Presets
Alarm in/out	4 Inputs / 1 Relay Output
Function	
Day & Night	Night / Auto / Day
Back Light	Off / HLC / BLC / WDR
White Balance	ATW/ AWC/ Manual/ Indoor/ Outdoor
DNR	Low/Middle/Max/Off
Privacy / Motion	8 Zones / 1 Zones
Color Level	Level Setting
Stibilize	On/Off
Environment	
Operating Humidity	30 % ~ 90 % RH
Operating Temp.	- 40°C to 50°
Electrical	
Power Consumption	Max 24W
Power Supply	AC24V, 50/60Hz

Mechanical	
Construction	Aluminum body , Clear vandal bubble (PC)
Dimension	261.8(W)X324.6(H)mm
Weight	About 4.6Kg (Camera Only)
Certificate	CE, FCC, IP66

