

IP PTZ Camera

10X, WDR, 1080P

DMC-10SEW

Picture



Feature

- 1/3" Panasonic PS-CMOS
- 2Megapixel H.264 IP PTZ Camera
- Optical 10x Zoom, Digital 32x Zoom, Auto Focus
- Day & Night with ICR. Low up to 0.003Lux with DSS(x32)
- WDR(120dB), Digital Image Stabilizer, 3D DNR
- Motion, Privacy Masking (8), Defog, Time Schedule, User Password
- Preset(250), Group(12), Tour, Trace, Alarm(1/1)
- Outdoor Type(IP66), Dehumidification, Fan/Heater
- Dual Encoding (H.264 / MJPEG)
- High Performance Streaming (Max. 30fps live view@1920x1080)
- Audio (1Input/1Output)

MODEL	DMC-10SEW
Video	
Image Sensor	1/3" 2Mega Panasonic CMOS
Scan mode	Progressive Scan
Total number of pixels	1,956(H) x 1,266(V), 2.4M Pixels
Number of active pixels	1,944(H) x 1,092(V), 2.3M Pixels
Resolution	1080P
Minimum illumination	Color : 0.5Lux , BW : 0.1Lux Min. 0.003Lux with DSS(32x)
S/N Ratio	50dB
Lens	
Lens	5.1~51mm(10x), F1.6 (wide) ~ F1.8 (tele) Optical(10x), Digital Zoom(32x), Total Zoom (320x)
Focus mode	Auto / Manual / Oneshot
Angle of view	D:68° (W)~67° (T), H:54°(W)~4.9°(T), V:31°(W)~4°(T)
Network	
Hardware	Flash (32Mbyte), RAM (256Mbyte) Ethernet:RJ-45(10/100BASE-T)
Video Output	Channel 1ch (CVBS) Compression H.264 & MJPEG Dual Codec FULL HD(1920X1080),HD(1280X720P), VGA(640X480),QVGA(320X240) Max. Frame rate 30/25 fps Bitrate control : CBR or VBR(64K~12Mbps)
Audio	Audio In(1), Audio Out(1),8 bit PCM (G711 u-law) 8Khz, Mono
Memory Slot	SD/SDHC Memory Slot/Max.32GB
Event	Alarm / Motion Detection : E-mail, FTP, Event, Noti- Service
Recording	Manual / Schedule / motion Detection / Sensor Event
Client Viewer	Web viewer, CMS, Max-i
Network Protocol	HTTP, TCP/IP, UDP, ARP, ICMP, RTP/RTSP/ DHCP, Telnet, FTP, ,NTP, DDNS, SMTP, UPNP, PPPoE, Onvif, PSIA
Pan/ Tilt	
Pan/Tilt angle	360° Endless / 92°
Pan Speed	0.1° ~ 240°/sec (64 Levels), Preset: 360°/sec
Preset point	250 Presets
Alarm in/out	1 Inputs / 1 Relay Output
Function	
Day & Night	Day / Auto Slow / Auto fast / Night
Back Light	WDR / HLC / BLC
White Balance	Auto/ Indoor/ Outdoor
DNR	Off / Low / Middle / Max / Auto
Privacy / Motion	8 Zones / 1 Zones
Defog	Off/Auto/Manual
Environment	
Operating Humidity	30 % ~ 90 % RH
Operating Temp.	- 40°C to 50°
Electrical	

Power Consumption	Max 16W
Power Supply	AC24V, 50/60Hz
Mechanical	
Construction	Aluminum body , Clear vandal bubble (PC)
Dimension	168mm(Diameter) x 175.6(Height) mm
Weight	About 3.5Kg

