

# IP IR Bullet Camera

4K, H.265, 54IR

## DMC-8054BZW

### Picture



### Feature

- 1/2.5" Sony 8.29M Pixels STARVIS CMOS
- High Performance Dual Streaming (Up to 30fps@4K)
- Low up to 0.01Lux(LED On:0Lux), Noise Reduction (2D/3D)
- Day/Night with ICR, 54 IR(IR Distance 40m)
- 3.6~11mm 4K DC Auto Iris Lens
- Motion Detection (4), Privacy Masking (8), Digital Zoom (16x)
- Defog, WDR, HLC, LDC (Lens Distortion Correction), Corridor
- Audio (1/1), Alarm (1/1), SD Slot, IP (66)
- ONVIF, DDNS, DHCP, CMS, Web Browser, Smart Phone
- Option: POE

MODEL	DMC-8054BZW
<b>Video</b>	
Image Sensor	Sony 1/2.5" 8.29Megapixel CMOS Sensor
Scan mode	Progressive Scan
Number of effective pixels	3840(H) x 2160(V) approx. 8.29M pixels
Minimum illumination	Color:0.1Lux, 0.01Lux with Sens-Up(10x)/F1.2, 50IRE,
Day & Night	Day & Night with ICR (TDN)
S/N Ratio	More than 54dB (AGC Off)
<b>Lens</b>	
Lens	3.6 ~ 11mm 4K Varifocal Lens H:90°(T)-37.6°(W), V:49.4°(T)-21.5°(W), D:104°(T)-43.3°(W)
Iris	DC Auto Iris
<b>Network</b>	
Video Compression	H.265, H.264, MJPEG
H.265/H.264 Profile	H.265 Main profile/H.264 Baseline.Main.High Profile
Ethernet	RJ-45(10/100BASE-T)
Frame Rate	3840x2160(4K), 2592x1944(5M), 2048x1536(QXGA), 1920x1080(Full-HD), 1280x1024(SXGA), 1280x720(HD), 704x480(4CIF/NT), 704x576(4CIF/PAL), 640x480(VGA), 352x288(CIF), 320x240(QVGA)
Video Frame Rate	Up to 30fps@3840x2160
Bitrate Control	CBR or VBR(100K~12Mbps)
Audio	Audio In(1), Audio Out(1), 8 bit PCM (G711 u-law) 8Khz, Mono
Memory SD Slot	SDHC/SDXC
Recording (SD)	Continuous / Event (Motion, Trigger, Alarm)
Event	Alarm In: Onboot/Trigger/Network Loss/Tampering/Motion Event Output :E-mail, FTP
Client Viewer	Web viewer, Max-i CMS
Max. User Connection	10 Users
Network Protocol	TCP/IP, UDP, IPv4/v6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, PPPoE, Onvif
<b>Function</b>	
Auto White Balance Mode	ATW-Indoor/Outdoor, Shade, Clear sky, Fluorescent light, Light bulb, Flame, Manual
Auto Exposure Mode	Automatic (Priority: Frame rate/Low noise), Manual
Gain Control	Automatic, Manual: Min. 1.2dB ~ Max. 54dB, Default 1.2dB
DNR	Off / Level Setting
Back Light	HLC, BLC, WDR(120dB)
Defog/LDC/Mirror/Flip	On/ Off
Privacy / Motion	8 Zones / 4 Zone
Alarm	1in/ 1out
IR Range	40m (54 IR LEDs)
<b>Environment</b>	
Operating Humidity	30 % ~ 90 % RH
Operating Temp.	-30°C~60°C(-22°F~140°F)
<b>Electrical</b>	
Power Consumption	Max 9.9W
Power Supply	DC12V±10,

**Mechanical**

Construction	Aluminum Body, Acrylic window
Dimension	88.6(W)X90.5(H)mm
Weight	About 1.5Kg

