



Model No.:KVM-1753W

Display Size:17"

Resolution:1920×1080

Aspect Ratio:16:9

Introduction:

KVM-1753W is a 17.3inch multi-functional monitor that supports full video formats.It provides with waveform, vectorscope,audio meter and more professional broadcast features.Built-in AC in and DC in power suppliers and efficient features makes it a nice choice for post-production,editing applications.

- 17.3" 1920×1080 native resolution
- 12Bit video processing
- 3D LUT color calibration
- 3G-SDI 4:4:4 12Bit signals (SMPTE 425M A/B)
- 2x2K/3G/HD-SDI in/out
- Composite/Component in/out
- PIP/PBP(size/position adjustable)
- Wide type/Waveform(waveform alarm)
- Waveform,Vectorscope,Audio Meter for SDI1,SDI2
- Waveform,Vectorscope,Audio Meter for HDMI
- Histogram
- Pixel Measurement

- Picture Flip,H/V Delay
- Focus Assist,Zoom
- False Color,Zebra
- Scan,Marker,Blue Only/Mono
- Audio Phase,Time Code
- Audio Meter (16ch SDI,2ch HDMI)
- Dynamic UMD(TSL3.1/4.0)
- Built-in DC IN /AC IN
- Power-off Memory
- Ethernet/GPI
- RS422 in/out

LCD	
Display Size	17.3"
High Resolution	1920×1080
Aspect Ratio	16:9
Wide Viewing Angle	178°(H) / 178°(V)
Pixel Pitch	0.1989×0.1989(mm)
Color Depth	16.7M
Back Light	LED
Brightness	300cd/m2
Contrast Ratio	700:1

Input

2 × BNC	SDI1/2 Channel Input (3G/HD/SD-SDI Auto-Detected)
3 × BNC	YPbPr/Video/Y/C
1 × DVI	DVI-I Input
1 × HDMI	HMDI input

Output

2 × BNC	SDI1/2 Channel Output (3G/HD/SD-SDI Auto-Detected)
3 × BNC	YPbPr/Video/Y/C

Compatible SDI Formats

SMPTE-425M-A/B	4:2:2 YCbCr 10-bit	1080p(50/59.94/60)
	4:4:4 YCbCr/RGB 10-bit 4:4:4 YCbCr/RGB 12-bit	1080i(60/59.94/50)
		1080p(30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)
	4:2:2 YCbCr 12-bit	1080i(60/59.94/50)
		1080p(30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)
4:4:4 YCbCr/RGB 10-bit	720p(60/59.94/50/30/29/25/24/23.98)	
SMPTE-274M	1080i(60/59.94/50)	
	1080p(30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)	
SMPTE-296M	720p(60/59.94/50/30/29/25/24/23.98)	
SMPTE-260M	1035i(60/59.94)	
SMPTE-125M	480i(59.94)	
ITU – R BT.656	576i(50)	

Audio In / Out

SDI Audio In	16 Channel Embedded Audio
Audio Meter Display(VU+PPM)	H/V Audio Level Meter Display
Analog Audio Input	3.5mm Headset Switch Cable
Audio Headset Output	3.5mm Headset Jack
Built-in Speaker	2.5W×2

General

Operating Temperature	-10°C~50°C
Input Voltage	DC : 12V / AC : 100-240V 50/60HZ

Power Consumption	26W
Power-Saving Mode	Turn off unimportant Key Automatically if No Signal Input
Accessory	Power Adaptor
Optional	DVI-HDMI adapter/Rackmount bracket/Wall-Mount VESA bracket