

- -
- Model No.:KFM-1753W
- Display Size:17"
- Resolution:1920x1080
- Aspect Ratio:16:9



Introduction:New 17" Full HD 3G/HD-SDI 1RU pull out rackmount monitor,full features with waveform/histogram/vectorscope/false color and 2 channels 3G-SDI signal di...

### Specifications

LCD	
Display Size	17"
High Resolution	Full HD 1920×1080
Aspect Ratio	16:9
Wide Viewing Angle	<b>178°(H) / 178°(V)</b>
Pixel Pitch	0.1989×0.1989(mm)
Color Depth	16.7M
Back Light	LED
Brightness	300cd/m2
Contrast Ratio	700:1

Input	
2 × BNC	SDI1/2 Channel Input ( <b>3G/HD/SD-SDI Auto-Detected</b> )
3 × BNC	YPbPr/Video/Y/C
1 × DVI	DVI/HDMI/VGA Input

Output	
2 × BNC	SDI1/2 Channel Output ( <b>3G/HD/SD-SDI Auto-Detected</b> )

Compatible SDI Formats		
SMPTE-425M-A/B	4:2:2 YCbCr 10-bit	1080p(50/59.94/60)
	4:4:4 YCbCr/RGB 10-bit	1080i(60/59.94/50)
	4:4:4 YCbCr/RGB 12-bit	1080p(30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)
	4:2:2 YCbCr 12-bit	1080i(60/59.94/50)
	4:4:4 YCbCr/RGB 10-bit	1080p(30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)
SMPTE-274M		720p(60/59.94/50/30/29/25/24/23.98)
		1080i(60/59.94/50)
		1080p(30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)
SMPTE-296M		720p(60/59.94/50/30/29/25/24/23.98)
SMPTE-260M		1035i(60/59.94)
SMPTE-125M		480i(59.94)
ITU – R BT.656		576i(50)

## Audio In / Out

SDI Audio In	8 Channel Embedded Audio
Audio Meter Display(VU+PPM)	H/V Audio Level Meter Display
Analog Audio Input	3.5mm Headset Switch Cable
Audio Headset Output	3.5mm Headset Jack
Built-in Speaker	2.5W×2

## General

Operating Temperature	-10°C~50°C
Input Voltage	DC 12V
Power Consumption	30W
Power-Saving Mode	Turn off unimportant Key Automatically if No Signal Input
Unit/Packing Dimension	580X550X160(mm)
Net/Gross Weight	8.9KG / 10.66KG
Shell Materials	Aluminum on Front-Shell/Base Supporter/Rust-Proof iron on Back-Shell
<b>Accessory</b>	Power Adaptor

*※specifications may be changed without prior notice.*

