

Model No.:KVM-1660W

Display Size:15.6"

Resolution:1920X1080

Aspect Ratio:16:9



Introduction:Newly published 15.6"supports 3D-LUT color calibration,3Gbs SDI 4:4:4 12Bit signals provided with waveform,vectorscope,histogram and other professiona...

Specifications

LCD	
Display Size	15.6"
High Resolution	Full HD 1920×1080
Aspect Ratio	16 : 9
Wide Viewing Angle	178°(H) / 178°(V)
Pixel Pitch	0.179×0.179(mm)
Color Depth	1.073G (True 10bit)
Back Light	LED
Brightness	210cd/m2
Contrast Ratio	700:1

Input	
2 × BNC	SDI1/2 Channel Input (3G/HD/SD-SDI Auto-Detected)
3 × BNC	YPbPr/Video/Y/C
1 × HDMI/DVI/VGA	HDMI/DVI/VGA Input
Output	
2 × BNC	SDI1/2 Channel Output (3G/HD/SD-SDI Auto-Detected)
3 × BNC	YPbPr/Video/Y/C

Compatible SDI Formats		
SMPTE-425M-A/B	4:2:2 YCbCr 10-bit	1080p(50/59.94/60)
	4:4:4 YCbCr/RGB 10-bit	1080i(60/59.94/50)
	4:4:4 YCbCr/RGB 12-bit	1080p(30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)
	4:2:2 YCbCr 12-bit	1080i(60/59.94/50)
	4:4:4 YCbCr/RGB 10-bit	1080p(30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)
SMPTE-274M		1080i(60/59.94/50)
		1080p(30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)
SMPTE-296M		720p(60/59.94/50/30/29/25/24/23.98)
SMPTE-260M		1035i(60/59.94)
SMPTE-125M		480i(59.94)
ITU— R BT.656		576i(50)

Audio In / Out	
SDI Audio In	8 Channel Embedded Audio

Audio Meter Display(VU+PPM)	H/V Audio Level Meter Display
Analog Audio Input	3.5mm Headset Switch Cable
Audio Headset Output	3.5mm Headset Jack
Built-in Speaker	2.5W×2
General	
Operating Temperature	-10°C~50°C
Input Voltage	DC 12V / AC 100-240V 50/60Hz
Power Consumption	31W
Power-Saving Mode	Turn off unimportant Key Automatically if No Signal Input
Unit Dimension	L376.9×H252.9×W72(mm)
Net Weight	3.48KG(Exclude desktop stand)
Shell Materials	Aluminum on Front-Shell/Base Supporter/Rust-Proof iron on Back-Shell
Accessory	Power Cord /Desktop stand
Optional	DVI-HDMI adapter/Wall-Mount VESA bracket

※specifications may be changed without prior notice.

