



Model No.:KVM-2461W

Display Size:24"

Resolution:1920×1080

Aspect Ratio:16 : 9

Introduction:24" FHD Premium Broadcast Monitor,multi-functional broadcast features,support user importing LUT tables into the monitor.

KVM-2461W is a cost-effective 24inch color grading monitor,applying 3D LUT color calibration technology,with good color image quality and color reproduction.KVM-2461W supports 2x3G/HD-SDI inputs and 2 outputs,equipped with waveform/ vectorscope,histogram,PIP&PBP, Pixel Meaurement and H/V embedded audio meter display etc functions under all SDI 1,SDI 2 and HDMI signals,it is a perfect solution for control rooms and post production facilities.

Product Highlight

- 24" 1920×1080 native resolution
- 12Bit video processing
- 3D LUT color calibration
- User importing Lut files into monitors
- Various Color Gamut : REC709(Gamma2.4)/REC2020/DCI-P3/SMPTE-C/EBU/USER)
- 3G-SDI 4:4:4 12Bit signals (SMPTE 425M A/B)
- 2x2K/3G/HD-SDI in/out
- Composite/Component in/out
- PIP/PBP(size/position adjustable)
- Wide type/Waveform(waveform alarm)
- Waveform,Vectorscope,Audio Meter for SDI1,SDI2
- Waveform,Vectorscope,Audio Meter for HMDI
- Histogram,Pixel Measurement
- Picture Flip,H/V Delay

- Focus Assist,Zoom
- False Color,Zebra
- Scan,Marker,Blue Only/Mono
- Audio Phase,Time Code
- Audio Meter (16ch SDI,2ch HMDI)
- Dynamic UMD(TSL3.1/4.0)
- Built-in DC IN /AC IN
- Power-off Memory
- Ethernet/GPI,RS422 in/out

Specifications

LCD	
Display Size	23.8"
High Resolution	Full HD 1920×1080
Aspect Ratio	16:9
Wide Viewing Angle	178°(H) / 178°(V)
Pixel Pitch	0.2745×0.2745(mm)
Color Depth	16.7M
Back Light	LED
Brightness	250cd/m2
Contrast Ratio	1000:1

Input

2 × BNC	SDI1/2 Channel Input (3G/HD/SD-SDI Auto-Detected)
3 × BNC	YPbPr/Video/Y/C
1 × DVI	DVI-I Input
1 × HMDI	HMDI input

Output

2 × BNC	SDI1/2 Channel Output (3G/HD/SD-SDI Auto-Detected)
3 × BNC	YPbPr/Video/Y/C

Compatible SDI Formats

SMPTE-425M-A/B	4:2:2 YCbCr 10-bit	1080p(50/59.94/60)
	4:4:4 YCbCr/RGB 10-bit	1080i(60/59.94/50)
	4:4:4 YCbCr/RGB 12-bit	1080p(30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)
	4:2:2 YCbCr 12-bit	1080i(60/59.94/50) 1080p(30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)
	4:4:4 YCbCr/RGB 10-bit	720p(60/59.94/50/30/29/25/24/23.98)
SMPTE-274M		1080i(60/59.94/50)
		1080p(30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)
SMPTE-296M		720p(60/59.94/50/30/29/25/24/23.98)
SMPTE-260M		1035i(60/59.94)
SMPTE-125M		480i(59.94)
ITU – R BT.656		576i(50)

Audio In / Out

SDI Audio In	16 Channel Embedded Audio
Audio Meter Display(VU+PPM)	H/V Audio Level Meter Display
Analog Audio Input	3.5mm Headset Switch Cable
Audio Headset Output	3.5mm Headset Jack
Built-in Speaker	2.5W×2

General

Operating Temperature	-10°C~50°C
Input Voltage	AC 100-240V 50/60Hz/ DC 12V
Power Consumption	37W
Power-Saving Mode	Turn off unimportant Key Automatically if No Signal Input
Shell Materials	Aluminum on Front-Shell/Base Supporter/Rust-Proof iron on Back-Shell
Accessory	Power Cord /Desktop stand
Optional	DVI-HMDI adapter/Wall-Mount VESA bracket

KVM-2461W is a cost-effective 24inch color grading monitor,applying 3D LUT color calibration technology,with good color image quality and color reproduction.KVM-2461W supports 2x3G/HD-SDI inputs and 2 outputs,equipped with waveform/vectorscope,histogram,PIP&PBP, Pixel Measurement and H/V embedded audio meter display etc functions und all SDI 1,SDI 2 and HMDI signals,it is a perfect solution for control rooms and post production facilities.