

VS0601 SPECIFICATIONS

Inputs	Video Inputs	SDI×4, HDMI×2
	SDI Input Format	1080p 60/59.94/50/30/29.97/25/24/23.98 1080psF 30/29.97/25/24/23.98 1080i 60/59.94/50 720p 60/59.94/50/30/29.97/25/24/23.98 625i 50 PAL, 525i 59.94 NTSC
	HDMI Input Format	1080p 60/59.94/50/30/29.97/25/24/23.98/23.976 1080i 50/59.94/60 720p 60/59.94/50/30/29.97/25/24/23.98 576i 50, 576p 50
	SDI Video Rate	Auto detection, SD/HD/3G-SDI
	SDI Compliance	SMPTE 259M/ SMPTE 292M/ SMPTE 424M
	Color Space and Precision	SDI: YUV 4:2:2, 10-bit; HDMI: RGB 444 8/10/12bit; YUV 444 8/10/12bit; YUV 422 8/10/12bit
	Outputs	PGM Outputs
PGM Output Format		1080p 60/50/30/25/24 1080i 50/60
Multiview Output		1×HD/3G-SDI; 1×HDMI Type A
Multiview Output Format		1080p 60
Audio	Audio Input	1×3.5mm Stereo audio; 1×RCA(L/R)
	Audio Output	1×RCA(L/R); 3.5mm 1× Stere audio
Others	GPIO	Tally
	LAN	RJ45
	Power	DC 12V, 2.75A
	Consumption	<33W
	Operation Temperature	-20°C~60°C
	Storage Temperature	-30°C~70°C
	Operation Humidity	20%~70%RH
	Dimension	375×271.5×43.7mm
	Weight	1kg
Warranty	2 Year Limited	
Accessories	Accessories	1×Power Supply (DC12V 5A), 1×User Manual