

Component Parameter Test Instruments

A. TH283X Series Compact LCR Meter

Features

- Low cost, high performance, small size
- 4.3 inch TFT LCD Display
- Soft power switch
- Selectable Chinese-English operation language
- Max. 200kHz test frequency
- Max. 6 digit reading resolution
- 10mVrms-2.0Vrms programmable signal level, built-in 0 - ± 5V/50mA bias source
- DCR, 50mV-2V programmable test level, resolution 10μΩ
- Ls-Rd / Lp-Rd Function (L, Rd display simultaneously) *
- Highest test speed 13ms/time
- Selectable 30Ω/100Ω signal source impedance
- V/I monitor and auto level adjustment function
- Built-in comparator, 10 bins sorting and count function
- File storage and firmware update through U disk
- RS232, RS485, USB, HANDLER, GPIB interface

* Rd means DCR.

NEW



TH283X Series

Rack mount (mm): 215(W) x 88(H) x 335(D)
 Dimension (mm): 235(W) x 105(H) x 360(D)
 Net weight: 3.6 kg

Brief Introduction

■ Adopting the latest technology & high density circuit design and concentrating the essence of LCR test, TH283X series is a new generation compact LCR meter of low cost and high performance. Instead of traditional mechanical power switch, it adopts software control power switch. The basic accuracy of 0.05% and good test stability can compare favourably with those high-end models. Being equipped with 4.3 inch TFT LCD Display and brand new interface system, TH283X series LCR meters possess elegant appearance and easy operation. Also, being provided with various interfaces and good compatibility with SCPI commands, TH283X series LCR meters are convenient for constituting all kinds of test system and satisfy various kinds of demands for inspection, production and scientific research.

Specifications

Model	TH2830	TH2831	TH2832
Basic measurement accuracy (See details in technical specification)	LCRZ	0.05%	0.1%
	DCR	0.1%	0.05%
Calibration condition	Warm up time: ≥ 30 minutes ; Environment temperature: 23±5°C Signal level: 1Vrms ; Corretion: after OPEN, SHORT Testing cable length: 0 m		
Test signal frequency	50Hz-100kHz , 34points 50Hz, 60Hz, 75Hz, 100Hz, 120Hz, 150Hz, 200Hz, 250Hz, 300Hz, 400Hz, 500Hz, 600Hz, 750Hz, 1kHz, 1.2kHz, 1.5kHz, 2kHz, 2.5kHz, 3kHz, 4kHz, 5kHz, 6kHz, 7.5kHz, 10kHz, 12kHz, 15kHz, 20kHz, 25kHz, 30kHz, 40kHz, 50kHz, 60kHz, 75kHz, 100kHz,	50Hz-200kHz , 37 points 50Hz, 60Hz, 75Hz, 100Hz, 120Hz, 150Hz, 200Hz, 250Hz, 300Hz, 400Hz, 500Hz, 600Hz, 750Hz, 1kHz, 1.2kHz, 1.5kHz, 2kHz, 2.5kHz, 3kHz, 4kHz, 5kHz, 6kHz, 7.5kHz, 10kHz, 12kHz, 15kHz, 20kHz, 25kHz, 30kHz, 40kHz, 50kHz, 60kHz, 75kHz, 100kHz, 120kHz, 150kHz, 200kHz	20Hz-200kHz , 15025 points
Signal source output impedance	Selectable 30Ω, 100Ω, ±1% @1kHz		

Component Parameter Test Instruments

A. TH283X Series Compact LCR Meter

AC test signal level	Normal	10mV—2Vrms		
		Resolution: 10mV, Accuracy: 10% x setting voltage+2mV		
	Constant level (ALC ON)	100μA—20mArms		
		Resolution: 0.1mA		
DCR test signal level		-----	-----	20mV—1Vrms
		-----	-----	Resolution: 10mV Accuracy: 10%
		-----	-----	200μA—10mArms
		-----	-----	Resolution: 0.1mA
DCR test signal level		1V DC	1V DC	50mV—2V DC
		-----	-----	Resolution: 0.5mV
DC bias voltage source		-----	-----	0V— ± 5V
		-----	-----	Resolution: 0.5mV, Accuracy: 1%
		-----	-----	0mA—± 50mA
		-----	-----	Resolution: 0.5μA
Test parameters	Z , Y , C, L, X, B, R, G, D, Q, θ, ΔCR			
DCR display range	0.00001 Ω – 99.9999 MΩ			
LCR parameters display range	Z , R, X 0.00001Ω — 99.9999MΩ Y , G, B 0.00001μs — 99.9999s C 0.00001pF — 9.99999F L 0.00001μH — 99.9999kH D 0.00001 — 9.99999 Q 0.00001 — 99999.9 θ(DEG) -179.999° — 179.999° θ(RAD) -3.14159 — 3.14159 Δ% -999.999% — 999.999%			
Display digits	6	5	6	
Measurement time (≥10 kHz)	Fast: 75 meas/sec(13ms), Medium:11 meas/sec(90 ms), Slow: 2.7meas/sec(370 ms)			
Equivalent circuit	Serial, Parallel			
Range mode	Auto, Hold			
Trigger mode	Internal, Manual, External, Bus			
Average time	1–255			
Correction	Open, Short, Load			
Math operation	Direct reading, ΔABS, Δ%			
Trigger delay time setting	0 - 60.000s, 1ms steps			
Step delay time setting	0 - 60.000s, 1ms steps			
List Sweep	·10 points list sweep ·Frequency, AC voltage/current, internal/ external bias voltage/ current can be swept. ·Each sweep point can be sorted separately.			
Comparator function	10 bins, BIN1–BIN9, NG, AUX			
	Bin count function			
	PASS, FAIL LED display on front panel			
Built-in Storage	Internal 100 LCRZ instrument setting files, 201 times test results			
USB Storage	Instrument setting files , measurement result CSV files, printed screen (GIF format)			
Interface	Control interface	HANDLER		
	Communication interface	USB HOST, RS232C, RS485(option), GPIB(option)		
	Storage interface	USB DEVICE (U-disk storage)		