

Model No.	9000C	9000D
Function	High/Low voltage AC current ,Leakage current ,Frequency, Transformer Core earthing current , Suitable for leakage current checking of mine and multi-core large cable	
Measuring Range	AC 0~6000A (50/60Hz Auto)	AC 0~20000A (50/60Hz Auto)
Frequency	45Hz~75Hz	
Resolution	10mA,0.1Hz	
Accuracy	0.00A~99.9A: $\pm 2\% \pm 5$	
	100A~6000A: $\pm 3\% \pm 5$	
	N/A	6.00kA~20.0kA : $\pm 4\% \pm 5$
Frequency Accuracy	± 1 Hz	
Sampling Speed	2times/S	
Live Voltage	Under 35kV bare wire Under 110KV insulated wire test (Test with insulation rod)	
Transmission	433MHz wireless , 150 meters	
Features		
Display	3.5inch Color LCD	
Data Storage	9999 Groups	
Peak Hold	√	
Date Hold	√	
Overflow Indication	√	
Auto Power Off	√	
Measurable Cable	Φ168mm Cable/ 168mmx245mm busbar	
Operation Way	Auto Range	
Insulation Rod Length	1M x 5pcs	
Backlight	√	
Low Battery Indication	√	
Insulation	AC 100kV/rms (between the 5th insulation rod and the clamp center)	
Working Condition	‘(-25~40)°C; below 80%Rh	
Storage Condition	‘(-10~60)°C; below 70%Rh	
General Information		

Power Supply	3.7V Rechargeable lithium battery
Product Size	Main Unit:250mm×100mm×40mm Clamp : 310mm×270mm×52mm
Product Weight	Main Unit:395g Clamp : 496g Insulation Rod : 1.45g Total : 11.5kg
Standard Accessories	Receiver x1pc,Clamp x1pc,Aerialx2pcs,Insulation Rod(1m)x5pcs,USB Cable+Charger x 1pc,Battery,Manual,Tool Case