



### Flat base

Comes with GH06F flat head features a flat base with a 3/8"-16 threaded mounting hole. This allows you to mount it in tripod legs with a 3/8"-16 threaded mounting screw, or 1/4"-20 screw with optional adapter. You can also mount optional jib arms or camera sliders that support flat base heads.



### "Real" Fluid Damping System

There are each 3+0 grades drag adjustment for Pan & Tilt, which helps you adjust the fluid head to suit your shooting style or the needs of the shot perfectly.



### "Real" Counterbalance System

5+0 steps for counterbalance that helps the fluid head support loads up to 6kg (13 pounds).



### "Snap-in" System

Thanks for the "Snap-in" design, you can attach the camera on the head not only by sliding the plate from front and back, but also snapped in from the top, very quickly.



(size:120x50x12mm)

### 501PL Universal Quick Release Plate

With Manfrotto 501PL plate, the camera can be assembled to other device which has same plate directly.



### Built In 1/4"-20 Threaded Hole

Built in 1/4"-20 thread hole for available monitor support arms or other accessory items.



### Bubble Level

An integrated bubble level on the head aids you in quickly leveling the fluid head.



### Including GB2 Telescope Handle

Extendable handle between 380-595mm (15-23.4in) for better reach or more precise movement.



### Precise Process And Skillful Assemble

CNC or Die-cast process for most parts to ensure enough precision. Hand-assembled and adjusted to precision by skillful senior worker at a time for each head.