

Specification		
Range	Resolution	Accuracy (23°C±5°C, <80%RH)
Phase : 0~360°	1°	±3°
Voltage: AC 0.00~600V	0.01V	±2%±3dgt
Current : AC 0.00mA~30.00A(50/60Hz auto)	0.01mA	±2%±3dgt
Frequency : 1.0Hz~400.0Hz	0.1Hz	±1Hz
Features		
Clamp Size	Φ7.5mm×13mm	
Display	4 digits LCD (35mm×21.5mm)	
Operation Way	Auto Range	
Data Storage	99 group	
Sample Rate	2 times/s	
Test Line Voltage	<600V	
Data Hold	√	
Data Recall	√	
Over Range Indication	Display " OL "	
Auto Power Off	15 minutes idle	
Low Battery Indication	√	
Working Current	Max 10mA	
Operation Condition	(-10~40)°C; <80%Rh	
Storage Condition	(-10~60)°C ; <70%Rh	
Insulation	2000V/rms	
Safety	IEC1010-1,IEC1010-2-032,Pollution 2,CAT III(600V)	
General Information		
Power Supply	9V 6F22	
Product Size	220mm×45mm×30mm	
Product Weight	220g	
Standard Accessories	Manual, Battery, Test Leads, Pouch	